

MATERIAL SAFETY DATA SHEET

HADDON EQUIPMENT & SUPPLIES
8441 MAIN STREET
VANCOUVER BC V5X 3Y2

Phone: (604) 325-3281
In Case of Emergency Only:
Phone CANUTEC: (613) 996-6666
Valid: Nov. 2011 – Nov. 2013

PRODUCT NAME:
CODE:
OTHER NAME: GREASE STRIP GEL
DISTRIBUTED BY:

GREASE-STRIP GEL
G518

WHMIS CLASSIFICATION: E
TDG CLASSIFICATION: SODIUM HYDROXIDE, SOLUTION; Class 8; UN 1824; PG II

HAZARDOUS INGREDIENTS	%WT/WT	CAS NO.	TOXICITY DATA (LD₅₀ & LC₅₀)
Sodium Hydroxide (50% Sol.)	10-30	1310-73-2	LD ₅₀ Oral (rat) 500 mg/kg ACGIH TLV - 2 mg/m ³
Monoethanolamine	3-7	141-43-5	LD ₅₀ Oral (rat) 1090 mg/kg LD ₅₀ Dermal (rabbit) 1000 mg/kg

PHYSICAL DATA FOR PRODUCT

Physical State: Liquid Sp. Gravity: 1.086 pH: 13.7 1% sol. - 11.9
Boiling Point: Not Avail. Vapour Pressure: Not Available
Vapour Density: N/A Evaporation Rate: Not Avail.
Freezing Point: Not Avail.
Solubility in Water: 100 %
Appearance & Odour: Colorless with slight odor, liquid.

FIRE AND EXPLOSION DATA FOR PRODUCT

Flash Point (Test Method): N/A
Flammable Limits in Air, % by vol. Non-flammable Lower: N/A Upper: N/A
Fire Extinguishing Substances: (X) Water Fog () Foam () CO₂
() Dry Chem () Other:
Hazardous Combustion Products: None

Special Firefighting Procedures: Use water spray to disperse vapours. Use self contained breathing apparatus and special protective clothing.

REACTIVITY DATA FOR PRODUCT

Incompatibility: () Water (X) Oxidizing Material (X) Acid () Base
(X) Other: Chlorinated hydrocarbons, ammonia, aluminum, tin, lead and zinc.

Hazardous Decomposition Products: Hydrogen (from contact with aluminum and other metals mentioned above).

Chemical Stability: Stable under normal conditions.

*N/A - Not applicable.

Product Name: GREASE-STRIP GEL (GREASE STRIP GEL)

HEALTH HAZARD INFORMATION FOR PRODUCT

EMERGENCY and FIRST AID PROCEDURES

Inhalation: Remove to fresh air and get medical attention.

Ingestion: Get medical help immediately. Rinse mouth well with water and give patient large quantities of water or milk to drink to dilute the chemical. Do not induce vomiting.

Eyes: Flush with plenty of water for at least 20 minutes. Get medical attention.

Skin: Remove contaminated clothing immediately and flush with water for at least 15 minutes. Get medical help. No oil or ointment should be applied.

EFFECTS OF OVEREXPOSURE (Acute and Chronic)

Inhalation: Mist may cause irritation of respiratory tract, inflammation of the lungs.

Ingestion: Burning in mouth and esophagus; nausea, vomiting, abdominal pain and diarrhea. Perforation of gastrointestinal tract may occur. May be fatal.

Eyes: Causes severe irritation to the mucous membranes of the eyes. May cause ulceration of the eye. Glaucoma, cataracts and permanent blindness may occur.

Skin: Severe irritation and burns to the skin. Damage may be delayed.

PREVENTIVE MEASURES

Steps to be taken upon release or spillage (including neutralizing):

With large spills, dyke for later disposal. neutralize with diluted acid - like hydrochloric or sulfuric acid. Minor spills can be neutralized and flushed with plenty of water.

Waste disposal method:

Waste product should not be discharged into sewers or streams. It should be first neutralized with dilute acid and then discharged according to federal, local and provincial regulations.

Handling and Storage Requirements:

Store in cool area above freezing point of product. When diluting always add product slowly to water to prevent boiling and splattering.

Ventilation Requirements (Local or General):

Use under well ventilated area.

Respiratory Protection:

A mask should be worn.

Eye Protection:

Chemical Workers goggles or full face shield.

Other Protection:

Rubber, vinyl or neoprene gloves and coveralls should be worn.

Prepared by: Technical Services Department, Ostrem Chemical Co. Ltd., Ph (780) 440-1911