

On-Premises
Soft Mount Washer-Extractor

255 lb Washer-Extractor



Expert Solutions from the Laundry Experts

Specifications

Tilt System (optional)

To improve loading and unloading ease, this model is available with a two-way tilt. Rear tilt for loading and front tilt for unloading. Also included with this feature is a jog switch to rotate the cylinder during loading/unloading.

Control

Programmable control including 20 fixed programs and 59 which can be customized. Other features include temperature controlled fill, six water levels, and graphic display cycle counter.



Chemical Dispensing

Five-compartment dry supply dispenser. Also includes nine liquid supply connectors.

High Speed Extract

Super high extract (380 G-Force) reduces drying time, saving labor and energy costs.

Five-Year Limited Parts Warranty

A five-year limited warranty is issued on the frame, basket, shaft, bearings and seals if failure or breakage should occur during normal operation due to defects in material or workmanship that would prohibit its further use. A three-year limited warranty also is issued to the original purchaser on all parts. Labor not included.



| | UVN255 | UVN255 (tilt) | |
|--|----------------|----------------|------------|
| Capacity - lb (kg) | 255 (110) | 255 (110) | |
| Width - in (mm) | 73" (1838) | 73" (1838) | |
| Depth - in (mm) | 81" (2058) | 81" (2058) | |
| Height - in (mm) | 81" (2068) | 89" (2256) | |
| Cylinder Diameter - in (mm) | 51 1/2" (1310) | 51 1/2" (1310) | |
| Cylinder Depth - in (mm) | 32" (816) | 32" (816) | |
| Cylinder Volume - cu. ft. (liters) | 38.9 (1100) | 38.9 (1100) | |
| Door Opening - in (mm) | 27" (686) | 27" (686) | |
| Door Bottom to Floor - in (mm) | 31 3/4" (807) | 39 3/16" (995) | |
| Water Inlet Connection - in (mm) | 2" (51) | 2" (51) | |
| Steam Connection - in (mm) | 1" (25.4) | 1" (25.4) | |
| Drain Diameter - in (mm) | 5" (127) | 5" (127) | |
| Motor Size - HP (kW) | 40 (30) | 40 (30) | |
| Independent Liquid Chemical Injection Connections on Rear - Qty. | 9 | 9 | |
| Independent Compartments on Side Mounted Dispenser - Qty. | 5 | 5 | |
| Voltage/Hz/Phase Circuit Breaker - FLA | 208/60/3 | 40-30.5 | 40-30.5 |
| | 240/60/3 | 40-26.5 | 40-26.5 |
| | 440/60/3 | 20-14.4 | 20-14.4 |
| | 480/60/3 | 20-13.2 | 20-13.2 |
| Domestic Shipping Dimensions - in (mm) | Width | 77" (1950) | 77" (1950) |
| | Depth | 84" (2120) | 84" (2120) |
| | Height | 89" (2245) | 89" (2245) |
| Net Weight - lb (kg) | 8417 (3818) | 9343 (4238) | |
| Shipping Weight - lb (kg) | 10,098 (4580) | 10,098 (4580) | |
| Tilt Crate Shipping Dimensions - in (mm) | Width | N/A | 43" (1092) |
| | Depth | N/A | 78" (1981) |
| | Height | N/A | 28" (711) |
| Tilt Crate Net Weight - lb (kg) | N/A | 423 (192) | |
| Tilt Crate Shipping Weight - lb (kg) | N/A | 475 (215) | |
| Agency Approvals* | ETL | ETL | |

* Agency approvals may vary depending on configuration. Consult factory for details.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2009 Alliance Laundry Systems LLC

www.uniwash.com

Alliance Laundry Systems
Shepard Street, Ripon, WI 54971 Telephone: 1-800-587-5458

